



E. Jordan Brookes
Engineered Metals and Plastics

COMPANY QUALITY PROFILE
In Business since 1936

LOCATION ADDRESS: Corporate Office	Street: 10634 Shoemaker Avenue	City: Santa Fe Springs	State: CA	Country: USA	Zip: 90670-4038
Mailing address: P.O. BOX 2220 Santa Fe Springs, CA 90670-2220			Website Address: www.ejbco.com		
Building: Owned	Total Floor space: 78,582 sq. ft.	Warehouse: 66,331 sq. ft.	Manufacturing: 12,251 sq. ft.		
Total employees: 58	Sales/Purchasing: 14	Quality: 1	Manufacturing: 31	Administration: 12	
NAICS Code:	423510				
QUALITY PROGRAM:	ISO 9001 + AS 9120		Expiration Date: February 9, 2020	Registration Number: 14014ASS001	Cage Code: 63G04
Company contacts	General Manager	Directors of Sales	Inside Sales Supervisor	Quality & Safety Manager	Director of Operations
Name	Lindsey Fisher	Ozzie Castro & Marty Kaplan	Carol Herkins	Eliza Acosta	Jon Quesenberry
Phone	562-968-2100	562-968-2100	562-968-2100	562-968-2100	562-968-2100
Fax	562-968-2110	562-968-2110	562-968-2110	562-968-2110	562-968-2110
E-Mail	lfisher@ejbco.com	ocastro@ejbco.com , mkaplan@ejbco.com	cherkins@ejbco.com	eacosta@ejbco.com	jonq@ejbco.com
Reports to	EJB Board	General Manager	Directors of Sales	General Manager	General Manager
LOCATION ADDRESS: Fremont Branch	Street: 4121 Business Center Drive	City: Fremont	State: CA	Country: USA	Zip: 94538
Building: Owned	Total Floor space: 13,000 sq. ft.	Warehouse: 9,000 sq. ft.	Manufacturing: 2,000 sq. ft.		
QUALITY PROGRAM:	ISO 9001 + AS 9120		Expiration Date: February 9, 2020	Registration Number: 14014ASS001	Cage Code: 63G04

Type of Business: Value Added Supplier of Engineered Metals and Plastics

Calibration Inspection to: ANSI-NCSL Z540, ISO 10012-1 Traceable to NIST

Hours of operation: Monday through Friday, 7am – 4pm Pacific Standard Time.

Manufacturing capabilities (not limited to):

Slitting; Thickness =.001 - .070, **Width** = .054 – 26”, Standard rule for width is 10 times the thickness.

Cut to Length Sheet; Thickness =.002 - .063, **Length** =2” – 144”, **Width** =½” – 24.5”, Check with sales.

Cut to length Bar Stock; 1/8” to 10” Diameter,

Tension Leveling; Thickness =.003 - .062, **Width** =¼” – 4”,

Traverse wind; Thickness = .007 - .050, **Width** =¼” – 2”, up to 4,000 lbs.,

Edge rolled to reduce burr; Thickness =.016 - .065, **Width** =¼” – 24.5”,

Edge Skived to remove burr; (Hard Temper or Greater) **Thickness** =.008 - .032, **Width** = ¼” – 2”.

All Customer #2 audits must be scheduled and approved before the audit.

Form filled out by: Eliza Acosta

Title: Quality & Safety Manager

Date: September 19, 2018

Quality\Forms\Quality\Master...\Company Quality Survey Profile CONTROLLED Print Date: 9/19/2018